

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
16 October 2003 (16.10.2003)

PCT

(10) International Publication Number
WO 03/085371 A2

- (51) International Patent Classification⁷: **G01N** (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (21) International Application Number: PCT/IL03/00292
- (22) International Filing Date: 7 April 2003 (07.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 149016 7 April 2002 (07.04.2002) IL
- (71) Applicant (*for all designated States except US*): **GREEN VISION SYSTEMS LTD.** [IL/IL]; 6 HaNachoshet Street, Ramat Hachayal, 69 710 Tel Aviv (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): **MOSHE, Danny, S.** [IL/IL]; 11 HaGilboa Street, 55 024 Kiryat Ono (IL).
- (74) Agent: **G. E. EHRLICH (1995) LTD.**; 28 Bezael Street, 52 521 Ramat Gan (IL).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: REAL TIME HIGH SPEED HIGH RESOLUTION HYPER-SPECTRAL IMAGING

(57) **Abstract:** Real time high speed high resolution hyper-spectral imaging. (a) electromagnetic radiation collimating element (16), collimating electromagnetic radiation (44) emitted by objects (12) in a scene or a sample (14); (b) optical interferometer (18), receiving and dividing collimated object emission beam, generating interference images, and piezoelectrically determining and changing magnitude of optical path difference of divided collimated object emission beam; optical interferometer (18) includes: beam splitter (20'), fixed mirror (22), movable mirror (24), piezoelectric motor (26), displacing movable mirror (24) along axis (60), distance change feedback sensor (28), sensing and measuring change in distance of movable mirror (24) along axis (60), piezoelectric motor controller (30), actuating and controlling piezoelectric motor (26); and thermo-mechanically stable optical interferometer mount (32A); (c) camera optics (34), focusing interference images of each optical path difference; (d) detector (36), recording interference images; (e) central programming and signal processing unit (38), and (f) display (40).